


2018	Product	Reynolite® aluminium composite panel
	Thickness	2mm, 3 mm and 4 mm
	Core	PE
	Paint	1 - coat polyester
	Length	From 2m to 6m
	Width	1,000 mm, 1,250 mm, 1,500 mm and 2,000 mm
	Weight	Reynolite® 2 mm: 2.7 kg / m ² ; 0.55 lb / ft ² Reynolite® 3 mm: 3.6 kg / m ² ; 0.74 lb / ft ² Reynolite® 4 mm: 4.6 kg / m ² ; 0.94 lb / ft ²
	Colour choice	All references listed below
	DELIVERY TERMS	
	Delivery terms departure Merxheim	<ul style="list-style-type: none"> The following deadlines apply to all orders communicated by Wednesday noon. Delivery times below according to minimum order quantity, width and thickness.



Digital Print
White 903 S

From 1 pallet*	2mm	3mm	4 mm
1,250 x 2,500 mm	see below	W+1	see below
1,500 x 3,050 mm	W+1	W+1	see below
1,500 x 4,050 mm	see below	W+1	see below
2,000 x 3,050 mm	see below	W+1	see below
2,000 x 4,050 mm	see below	see below	see below

Other dimensions: 1,000sqm, W+4 (except for 2,000mm wide, please consult us)
*According to palletising



Red 320 S



Silver 906 S



Black 905 S



Yellow 123 S



Blue 502 S

From 1.000 sqm**	2mm	3mm
1,500 mm width	W+4	W+4

Front: Satin
Back: Satin (same colour as front side)
**Tolerance on quantity: +/- 10%
Do not mix Reynolite® with Reynobond®

Disclaimer

Laws and building and safety codes governing the design and use of Arconic Architectural Products SAS's (AAP) products, and specifically aluminium composite materials, vary widely. It is the responsibility of the owner, the architect, the general contractor, the installer and the fabricator/transformer, consistent with their roles, to determine the appropriate materials for a project in strict conformity to all applicable national, regional and local building codes and regulations. PE products are not available for purchase from AAP for consideration in architectural applications. As Reynobond's reaction to fire varies according to its core, please ensure the product is used in a system that complies with applicable fire safety regulation.