

Anodized Reynobond Panels

Arconic Architectural Products LLC (AAP) is pleased to announce that we now offer Anodized Reynobond® composite panel. Anodized Reynobond® panels are available in 4mm thickness in FR core, 50” and 62” widths. Please inquire for product lead times.

Because of color variation typical in the anodizing process, the following considerations must be taken when ordering Anodized Reynobond® composite panels:

- Order one width per project (50” or 62”) due to color variation from coil to coil.
- Panels should be erected in one direction.
- There will be color variation between coils, please keep this in mind when more than one coil is needed to complete a project.
- Because color variation is likely to occur when ordering additional panels, an overage of panels should be ordered in case of damage during fabrication or installation of panels.
- Be aware that crazing of panels will occur during rolling, forming or bending of the material.
 - Add 2” for panels up to 8’ long
 - Add 4” for panels more than 8’ long

Samples are available upon request. Please call your sales manager or customer service representative at 800-841-774 for more information and availability or visit our website at www.reynobond.com or www.arconicarchitecturalproducts.com

Disclaimer

Laws and building and safety codes governing the design and use of AAP’s products, and specifically aluminum composite materials, vary widely. It is the responsibility of the owner, the architect, the general contractor, the installer and the fabricator/transformer, consistent with their roles, to determine the appropriate materials for a project in strict conformity to all applicable national, regional and local building codes and regulations. REYNOBOND IS COMBUSTIBLE; IT COULD CATCH FIRE AND BURN. SEE AAP WEBSITE FOR PRODUCT WARNINGS. ANY LABORATORY TESTING INFORMATION PROVIDED BY AAP APPLIES ONLY TO THE PARTICULAR PRODUCT OR ASSEMBLY TESTED AND DOES NOT NECESSARILY REPRESENT HOW PRODUCTS WILL ACTUALLY PERFORM IN USE.