

Alcoa® Ultra ONE® 22.5" x 9" Wheels



Less Weight, Better Fuel Economy and More Payload.

We've upped the ante. Alcoa® Ultra ONE® 22.5" x 9" Wheels utilize proprietary MagnaForce® alloy to save you more than 50 lbs. versus a comparable steel wheel for improved productivity at a class-leading load rating.

Tough Jobs Demand Tough Wheels.

Refuse collection, logging, mining and other heavy haul applications demand a tough wheel. These wheels are built for your toughest jobs.

A True Lightweight Heavyweight.

Each wheel offers a 10,000 lb. load rating. Yet at just 48 or 56 lbs., based on fitment, these wheels are the lightest in the market.


Additional Benefits

One piece forged strength that's 5x stronger than steel.

No painting. Lower maintenance costs.

True cool running extends tire and brake life.

Same five year limited warranty you've come to expect.



Improved Security

Increased aluminum wheel mounting flange thickness for improved fastener torque retention, providing maximum grip length.





89U63x



89U64x

Keep rolling with us at:



Alcoa® Ultra ONE® 22.5" x 9" Wheels

WHEEL SPECIFICATIONS

Alcoa® aluminum disc wheel mounting dimensions are consistent with SAE Recommended Practice J694 June 2007.

Hub Pilot - 10 Bolt Holes, 285.75mm Bolt Circle, 220.1mm Bore

Size	P/N	Weight (lbs)	Finish Options	SURFACE TREATMENTS				Bolt Hole Dia.	OFFSET		LOAD RATING		Valve Stem
				Dura-Black™	Dura-Bright®	Dura-Flange®	Dura-Bright® Dura-Flange®		Outset	Inset	Max Load (lbs)	Max Infl. PSI	
22.5 x 9	89U63x*	48	1, 7		1DB			26mm	N/A	3.12"	10000	130	TR555E
22.5 x 9	89U64x	56	1, 2, 3, 7	BLK	0DB, 1DB, 2DB, 3DB	7DF	3DD	26mm	6.94"	5.99"	10000	130	TR554D

* 0 and 7 finish options on certain wheels are determined by inset or outset mounting positions and may not be finished on both sides. See chart for position and available finish options.

SURFACE OPTION CODES

0 Brush Finish on both sides as applicable	7 Clean Buff Finish on both sides as applicable
1 Polished Outside Only	8 Clean Buff Finish on both sides. Reference data table for offset position
2 Polished Inside Only	9 Brush Finish on both sides. Reference data table for offset position
3 Polished Both Sides	
DB Dura-Bright® Surface Treatment	BLK Dura-Black™ Surface Treatment
DF Dura-Flange® Wear Protection	DD Dura-Bright® and Dura-Flange® Wear Protection



89U63x



For more information including accessories, call (800) 242-9898 or visit www.alcoawheels.com.