

Alcoa® 12.25" - 13.00" Wide Base Wheels



Tough Hauls Demand Tough Wheels

Demand only the best. From 12.25" to 13.00" in width, these wheels utilize proven LvL ONE® technology to reduce weight and optimize performance. Ranging from just 60 to 76 lbs. depending on part number, each wheel is a lightweight heavyweight in its class.

The Right Tool For a Tough Job

Refuse collection, logging, mining and other heavy haul applications demand a tough wheel. Spec the only aluminum wheels built for your tough job.

Less Weight, Better Fuel Economy, More Payload

Our proven LvL ONE® technology significantly reduces wheel weight versus comparable aluminum and steel wheels.

A True Lightweight Heavyweight

These wheels offer up to a 13,000 lb. load rating.

Additional Benefits

One piece forged strength that's 5x stronger than steel.



No painting, lower maintenance costs.

True cool running extends tire and brake life.

Five year limited warranty you've come to expect.



Keep rolling with us at:



www.alcoawheels.com

Arconic Wheel and Transportation Products

| 1616 Harvard Ave., Cleveland, OH 44105 |

(800) 242-9898



Alcoa® 12.25" – 13.00" Wide Base Wheels

WHEEL SPECIFICATIONS

Alcoa® aluminum disc wheel mounting dimensions are consistent with SAE Recommended Practice J694 June 2007.

	Bolt Holes, Bolt Circle, Hub Bore	Size	P/N	Weight (lbs)	Finish Options	SURFACE TREATMENTS		OFFSET		LOAD RATING		Valve Stem
						Dura- Black™	Dura- Bright®	Outset	Inset	Max Load (lbs)	Max Infl. PSI	
Ball Seat	10 Holes 11.25" Bolt Circle 8.72" Hub Bore	22.5 x 12.25	82305x	64	7			3.88"	N/A	11400	130	TR553E
								N/A	2.75"			TR555E
		22.5 x 12.25	82306x	69	7			N/A	4.68"	11000	130	TR555E
Hub Pilot	10 Holes 285.75mm Bolt Circle 220.1mm Hub Bore	22.5 x 12.25	82262x*	60	2, 7		2DB	0.56"	N/A	12300	130	TR553E
		22.5 X 12.25	82362x	62	2, 7		2DB	3.88"	N/A	12300	130	TR553E
					1, 8	1DB	N/A	2.75"	TR555E			
		22.5 X 12.25	82462x*	66	1, 7	BLK	1DB	N/A	4.68"	12300	130	TR552
		22.5 x 13	83U65x	63	2, 7		2DB	3.50"	N/A	13000	130	TR553E
	1, 8				1DB	N/A	2.38"	TR555E				
	22.5 x 13	83462x*	71	1, 7		0DB, 1DB	N/A	5.30"	12800	130	TR552	
10 Holes, 335 mm Bolt Circle 281.2mm Hub Bore	83358x*	76	1, 7		0DB, 1DB	N/A	6.12"	12800	130	TR553		

* 0 and 7 finish options on wide base wheels are determined by inset or outset mounting positions and may not be finished on both sides. See chart for position and available finish options.

SURFACE OPTION CODES

0 Brush Finish on both sides as applicable	7 Clean Buff Finish on both sides as applicable
1 Polished Outside Only	8 Clean Buff Finish on both sides. Reference data table for offset position
2 Polished Inside Only	9 Brush Finish on both sides. Reference data table for offset position
3 Polished Both Sides	
DB Dura-Bright® Surface Treatment	BLK Dura-Black™ Surface Treatment
DF Dura-Flange® Wear Protection	DD Dura-Bright® and Dura-Flange® Wear Protection



For more information including accessories, call (800) 242-9898 or visit www.alcoawheels.com.