

Alcoa® LvL ONE® 22.5" x 8.25" Wheels



Still The ONE.

Alcoa® LvL ONE® 22.5" x 8.25" Wheels utilize proven technology to lower weight, enhance strength and provide an eye-catching brightness second to none. Put 18 Alcoa LvL ONE® Wheels on a tractor trailer to reduce another 450 lbs. from your rig versus a set of standard steel wheels. For even lighter weight, spec Alcoa's Ultra ONE® Wheels with MagnaForce® alloy.

- Proven LvL ONE® process technology results in a brilliant finish on both sides for the Clean Buff '7' finish option.
- Increase payload or improve fuel efficiency.
- Each wheel offers a 7,400 load rating, but weighs just 45 lbs.

Additional Benefits

One piece forged aluminum strength that's 5x stronger than steel.

7,400 lb. load rating and 130 psi inflation rating.

The same five year limited warranty you've come to expect.



Keep rolling with us at:



@alcoawheels



facebook.com/alcoawheels



alcoawheels



youtube.com/AlcoaWheelsNorthAmerica



www.alcoawheels.com

Arconic Wheel and Transportation Products

1616 Harvard Ave., Cleveland, OH 44105

(800) 242-9898



Alcoa® LvL ONE® 22.5" x 8.25" Wheels

WHEEL SPECIFICATIONS

Alcoa® aluminum disc wheel mounting dimensions are consistent with SAE Recommended Practice J694 June 2007.

Hub Pilot - 10 Bolt Holes, 285.75mm Bolt Circle, 220.1mm Bore

Size	P/N	Weight (lbs)	Finish Options	SURFACE TREATMENTS			Bolt Hole Dia.	OFFSET		LOAD RATING		Valve Stem
				Dura-Bright®	Dura-Flange®	Dura-Bright® Dura-Flange®		Outset	Inset	Max Load (lbs)	Max Infl. PSI	
22.5 x 8.25	88367x	45	1, 2, 3, 7	0DB, 1DB, 2DB, 3DB	1DF, 2DF, 7DF	1DD, 2DD, 3DD	26mm	6.60"	5.79"	7400	130	TR554D

SURFACE OPTION CODES

0 Brush Finish on both sides as applicable	7 Clean Buff Finish on both sides as applicable
1 Polished Outside Only	8 Clean Buff Finish on both sides. Reference data table for offset position
2 Polished Inside Only	9 Brush Finish on both sides. Reference data table for offset position
3 Polished Both Sides	
DB Dura-Bright® Surface Treatment	BLK Dura-Black™ Surface Treatment
DF Dura-Flange® Wear Protection	DD Dura-Bright® and Dura-Flange® Wear Protection



For more information including accessories, call (800) 242-9898 or visit www.alcoawheels.com.